

耐酸鹼熱電阻 RTD Sensor for Acid/Alkali Application

- ◆ 能完全阻絕濕氣、腐蝕性及酸鹼性物質的熱電阻溫度計
- ◆ *Flexible sealed Teflon RTD Sensor for wet, corrosive, and acid/alkali materials*

THERMOWAY 的耐酸鹼熱電阻溫度計以雙層 Teflon 套管加強封底，可以做到完全防漏，完美隔離液體、腐蝕性物質、及酸鹼介質等。主要應用在半導體化學酸洗槽。

THERMOWAY 提供客製化服務，可依照需求訂製不同的熱電阻類別及型式，多種接頭可供選擇。



THERMOWAY's acid/alkali-resistant RTD sensors are sealed with a double-layer Teflon tubing, providing a completely leak-proof design and perfect isolation from liquids, corrosive substances, and acid and alkali media. They are primarily used in semiconductor chemical pickling tanks.

THERMOWAY offers customized services, tailoring various RTD types and styles to meet specific requirements. A variety of connectors are available.

Features

- Teflon 材質具有比不銹鋼更優異的耐化學腐蝕性能
- Teflon (PTFE and PFA) Tubing offers superior chemical-proof quality beyond that of stainless steel
- 彈性套管可用於具有彎曲部分和內部管道的裝置。
- Flexible tube can be used on devices with curved sections and inside pipes.
- 高精度選擇: DIN A, 1/3 DIN, 1/5 DIN, and 1/10 DIN
- High Accuracy: DIN A, 1/3 DIN, 1/5 DIN, and 1/10 DIN
- 工作溫度範圍: -190 ~ 260°C
- Working temperature range: -190 ~ 260°C
- 套管材質選擇: Teflon PTFE, PFA
- Tube selection: Teflon PTFE, PFA
- RTD 類別: PT100, PT1000, PT200
- RTD Symbol: PT100, PT1000, PT200



聯絡我們 Contact

崧啟工業股份有限公司 22183 新北市汐止區大同路二段 147 號 7 樓
7F, No.147, Tatung Road, Sec.2, Sijhih, New Taipei City, Taiwan, 22183
tel: +886-(0)2-8692-6689 fax: +886-(0)2-8692-6669 email: info@thermoway.com
www.thermoway.com

THERMOWAY INDUSTRIAL CO., LTD.